BUTTERWORTH HEINEMANN

INDEX

Author/Title Index

Annaswamy, A. M.: See Smith, M. H.

Bardoel, W.: See Dirksen, P.
Bifano, T. G.: See Drueding, T. W.
Birch, K. P.: See Downs, M. J.
Bissell, C. C.
  Control engineering, 298
Brand, U., and Hillmann, W.
  Calibration of step height standards for nanometrology using interference microscopy and stylus profilometry, 22
Brunner, C.: See Slocum, A. H.
Bucher, A.: See Sourlier, D.

Campbell, A.
  Measurement of lathe Z-slide straightness and parallelism using a flat land, 207
Carr, K., and Ferreira, P.
  Verification of form tolerances Part I: basic issues, flatness, and straightness, 131
  Verification of form tolerances Part II: cylindricity and straightness of a median line, 144
Chao, P-Y.: See Su, Y-T.
Chizhik, S. A., Gorbunov, V. V., and Myshkin, N. K.
  Analysis of molecular scale roughness effect on contact of solids based on computer modeling, 186
Cox, M. G.: See Downs, M. J.

Dirksen, P., Werf, J. v. d., and Bardoel, W.
  Novel two-frequency laser, 114
Downs, M. J., Birch, K. P., Cox, M. G., and Nunn, J. W.
  Verification of a polarization-insensitive optical interferometer system with subnanometric capability, 84
Drueding, T. W., Bifano, T. G., and Fawcett, S. C.
  Contouring algorithm for ion figuring, 10

Eltzert, E.: See Weckenmann, A.
Engelhaupt, D.: See Fawcett, S. C.

Fang, Z., Gu, Y., Yang, Y., and Yin, C.
  Data processing of the two-channel adaptive straightness measurement system based on optical activity, 253
Fawcett, S. C.: See Drueding, T. W.
Fawcett, S. C., and Engelhaupt, D.
  Development of Wolter I x-ray optics by diamond turning and electrochemical replication, 290
Ferreira, P.: See Carr, K.

Garmer, M.: See Weckenmann, A.
Ge, P., and Jouaneh, M.
  Modeling hysteresis in piezoceramic actuators, 211
Gorbunov, V. V.: See Chizhik, S. A.
Gu, Y.: See Fang, Z.

Hillman, W.: See Brand, U.
Horaguchi, I.: See Yamaguchi, K.
Hosoe, S.
  Highly precise and stable displacement-measuring laser interferometer with differential optical paths, 258
Hsiau, J-S.: See Su, Y-T.
Hwang, Y-D.: See Su, Y-T.

Isono, Y.: See Tanaka, T.

Jianhua, Z.: See Zhixin, J.
Jouaneh, M.: See Ge, P.

Kami, Y.: See Mizumoto, H.
Kanada, T.
  Evaluation of spherical form errors—computation of sphericity by means of minimum zone method and some examinations with using simulated data, 281
Kane, N. R.: See Slocum, A. H.
Kyusojin, A.: See Oiwa, T.

Mizumoto, H., Yabuya, M., Shimizu, T., and Kami, Y.
  An angstrom-positioning system using a twist-roller friction drive, 57
Myshkin, N. K.: See Chizhik, S. A.

Noguchi, S., Tsukada, T., and Sakamoto, A.
  Evaluation method to determine radial accuracy of high-precision rotating spindle units, 266
Nunn, J. W.: See Downs, M. J.

Oiwa, T., and Kyusojin, A.
  Study of cylindrical grinding using ball and cone centers: static and dynamic characteristics of cone and ball center systems, 34

Rao, G. S., and Ro, P. I.
  Submicrometer control of a traction drive using state feedback and estimation, 124
Rivin, E. I.
  Vibration isolation of precision equipment, 41
Ro, P. I.: See Rao, G. S.

Sakamoto, A.: See Noguchi, S.
Scagnetti, P. A.: See Slocum, A. H.
Shimizu, T.: See Mizumoto, H.
Slocum, A. H.: See Smith, M. H.
Slocum, A. H., Scagnetti, P. A., Kane, N. R., and Brunner, C.
  Design of self-compensation, water-hydrostatic bearings, 173
Smith, M. H., Annaswamy, A. M., and Slocum, A. H.
  Adaptive control strategies for a precision machine tool axis, 192
Smith, S. T.: See Xu, Y.
Sourlier, D., and Bucher, A.
  Surface-independent, theoretically exact bestfit for arbitrary sculptured, complex, or standard geometries, 101
Su, Y-T., Wang, S-Y., Chao, P-Y., Hwang, Y-D., and Hsiau, J-S.
  Investigation of elastic emission machining process: lubrication effects, 164

Tanaka, T., Isono, Y., and Ueda, S.
  Influences of surface roughness and phase transformations induced by grinding on the strength of ZrO_2-Y_2O_3, 117
Thomas, G.: See Drueding, T. W.
Tsukada, T.: See Noguchi, S.

Precision Engineering 17:315–316, 1995

© Elsevier Science Inc., 1995

655 Avenue of the Americas, New York, NY 10010

0141-6359/95/$10.00
SSDI 0141-6359(95)00048-8

Ueda, S.: See Tanaka, T.

Wang, S-Y.: See Su, Y-T.
Wang, W. L., and Whitehouse, D. J.
Method for setting fidelity criteria for surface-measuring instruments, 274
Weber, H.: See Weckenmann, A.
Weckenmann, A., Eltzert, E., Garmer, M., and Weber, H.
Functionality-oriented evaluation and sampling strategy in coordinate metrology, 244
Werf, J. v. d.: See Dirksen, P.
Whitehouse, D. J.: See Wang, W. L.

Xing, A.: See Zhixin, J.
Xu, Y., and Smith, S. T.
Determination of squeeze film damping in capacitance-based cantilever force probes, 94

Yabuya, M.: See Mizumoto, H.
Yamaguchi, K., and Horaguchi, I.
Development of directionally aligned SiC whisker wheel, 5
Yang, Y.: See Fang, Z.
Yin, C.: See Fang, Z.

Zhixin, J., Xing, A., and Jianhua, Z.
Study on mechanical pulse electric discharge machining, 89

Keyword Index

Adaptive control, 192
Adaptive control with saturation, 192
Adaptive noise-cancelling technique, 253
Adaptive phase lead compensator, 192
Adaptive PID, 192
Adhesion, 186
Air spindle, 266
Alignment, 253
Angstrom-positioning, 57
Aperture correction, 22
Application condition, 281
Aspheric generator, 57
Athermal glass, 258
Atomic force microscopes, 186

Ball machine center, 34
Bestfit, 101
Bestfit algorithm, 101

Calibration, 22
Chatter stability, 34
Complex geometries, 101
Cone machine center, 34
Coordinate measuring machine, 131, 144
Coordinate measuring technique, 101
Coordinate metrology, 244
Critical damping ratio, 94
Cylindrical grinding, 34
Cylindrical size, 144
Cylindricity, 144

Damping, 41
Damping ratio, 34
Depth setting standard, 22
Diamond turning, 290
Differential interferometer, 258
Digital deconvolution, 274
Dimensional metrology, 101
Directional alignment, 5
Displacement measurement, 258
Dynamic characteristics, 34

Elastic emission machining process, 164
Electric discharge machining, 89
Error motion, 266

Face grinding, 5
Flatness, 131
Force probe, 94
Friction drive, 57
Functionality-oriented evaluation methods, 244

Grinding wheel, 5

Hard and brittle materials, 89
Heterodyne interferometry, 115
Hydrostatic bearing, 57
Hydrostatic bearings, 173
Hysteresis, 211

Inspection, 131, 144
Interference microscopy, 22
Isolation, 41

Least-squares method, 281
Lissajous' figure, 266
Lubrication effect, 164

Machine tool, 57
Machine tool axis, 192
Material removal rate, 89
Maximum inscribed cylinder, 144
Measurement strategy, 244
Minimum circumscribed cylinder, 144
Minimum zone method, 131, 281
Minimum zone solution, 144
Molecular scale, 186

Nanometrology, 22
Nanotechnology, 57
Natural frequency, 34
Nonlinear optimization, 281

Optical measurement, 115
Optical techniques, 258

PID control, 192
Piezoceramic actuators, 211
Positioning, 57, 192
Positioning accuracy, 57
Precision, 41
Precision grinding, 5
Precision machine, 192
Precision positioning, 125
Preisach model, 211
Production metrology, 244

Quality management, 244
Quartz, 258

Radial error motion, 266
Real contact area, 186
Replicated optics, 290
Resinoid wheel, 5
Reversal, 207
Robust control, 192
Rotation accuracy, 266
Roundness, 281

Sampling strategy, 244
Scanning, 186
Sculptured surfaces, 101
Self-compensated, 173
Shear stress, 164
SiC whisker, 5
Simulation, 281
Single-point diamond machining, 207
Sphericity, 281
Spindle, 266
Squeeze film damping, 173
Squeeze film force, 94
Stability, 258
State feedback, 125
Step height standard, 22
Straight-edge, 207
Straightness, 131, 144, 207, 253
Stylus instrument, 22
Surface damage, 274
Surface finish, 5
Surface harmonics, 281
Surface instrumentation, 274
Surface roughness, 5
Surface texture, 274

Thermal drift, 258
Three-dimensional (3-D) measuring technique, 101
Traction drive, 125
Tunneling, 186
Twist-roller friction drive, 57
Two-frequency laser, 115

Ultraprecision machine tool, 57
Ultrasonic vibration, 89

Vector, 266
Vibration, 41

X-ray, 290